

Soap_LicenseOrder

The information on this page refers to SOAP version 3, which includes additional fields. If you are using SOAP version 2, please refer to the [SOAP version 2 documentation](#).

The Soap_LicenseOrder object represents a license order in LAC. This object is used to add/edit license orders for a logged-in vendor.

Soap_LicenseOrder contains the following properties:

Property name	Type	Description
<i>customer_id</i>	integer	ID of the customer that the license order was created for.
<i>product_template_id</i>	integer	ID of the product template used to create the license order.
<i>activation_key</i>	string	Activation key of the license order.
<i>creation_time</i>	string	Creation time of the license order, in the format YYYY-MM-DD HH:MM:SS (for example, 2011-11-08 08:36:53).
<i>license_type</i>	string	Type of license for the license order. The possible values are as follows. local: Local license. network: Network license.
<i>licensee_type</i>	string	Type of licensee for the license order. The possible values are as follows. fixed: Fixed string value. customer: Licensee is set to customer name. not_specified: No licensee is specified.
<i>licensee</i>	string	Licensee for the license order. Required when <i>licensee_type</i> is set to fixed.
<i>hostid_match_rate</i>	integer	HostID match rate percentage required for license activation for the license order.
<i>min_hostids</i>	integer	Total minimum number of HostIDs required for license activation for the license order.
<i>activated_licenses_count</i>	integer	Number of activated licenses for the license order.
<i>enabled</i>	boolean	Specifies whether the license order is enabled or disabled.
<i>description</i>	string	Description of the license order.
<i>Hostids</i>	ArrayOfSoap_Hostid	Array of HostIDs for the license order.
<i>Features</i>	ArrayOfSoap_Feature	Array of Features for the license order.
<i>settings_description</i>	string	Description for the license order's Settings.
<i>removal</i>	boolean	Flag to specify whether the license should be removed from the end user's machine.
<i>removal_request_time</i>	string	Time that the <i>removal</i> flag was set to true.
<i>removal_confirmation_time</i>	string	Time that the end user sent information that the license was removed.
<i>deactivations_allowed</i>	integer	Number of deactivations allowed for end user.
<i>deactivations_left</i>	integer	Number of deactivations that remain.
<i>activations_allowed</i>	integer	Number of bulk licenses that can be activated for the license order.