

DeactivateLicense

The information on this page refers to SOAP version 2, which added this function. SOAP version 1 does not include this function.

The DeactivateLicense function is used to deactivate a license. For example, after deactivating a license, it can then be reactivated using a different host. This function requires an activation key and a HostID. Examples of a request and response for DeactivateLicense are given below.

Note that the response for DeactivateLicense will contain SUCCESS if successful or an error message if unsuccessful. See [Return Codes](#) for more information about error messages.

Example request

```
<soapenv:Envelope
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:ns="https://license.x-formation.com/soap/type/enduser/version/2">
  <soapenv:Header/>
  <soapenv:Body>
    <ns:DeactivateLicense soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
      <activationKey xsi:type="xsd:string">9RTV8-YX2P3-E53Q8-10AB6</activationKey>
      <hostid xsi:type="xsd:string">not_specified</hostid>
    </ns:DeactivateLicense>
  </soapenv:Body>
</soapenv:Envelope>
```

Example response

```
<SOAP-ENV:Envelope SOAP-ENV:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:ns1="https://license.x-formation.com/soap/type/enduser/version/2"
xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/">
  <SOAP-ENV:Body>
    <ns1:DeactivateLicenseResponse>
      <return xsi:type="ns1:Soap_Response">
        <result_code xsi:type="xsd:int">0</result_code>
        <result_string xsi:nil="true"/>
      </return>
    </ns1:DeactivateLicenseResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```