

ResetDeactivationCounter

The information on this page refers to SOAP version 2. This function does not exist in SOAP version 1.

The ResetDeactivationCounter function is used to reset the deactivation counter for a license order using a specified activation key.

This function requires an activation key, which can be obtained using the [GetLicenseOrderList](#) function, and a login token, which is obtained using the [Login](#) function.

Return values

On failure, the result string contains an error message. See [SOAP API return codes](#) for further information on error messages.

Example request

```
<soapenv:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:ns="https://license.x-formation.com/soap/type/vendor/version/2">
  <soapenv:Header/>
  <soapenv:Body>
    <ns:ResetDeactivationCounter soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
      <token xsi:type="xsd:string">dfe34ea4e14ed0be9c25002abf8b3986dd5fe22b</token>
      <activationKey xsi:type="xsd:string">KYZAV-OB4XS-ZJTN4-P2AVA</activationKey>
    </ns:ResetDeactivationCounter>
  </soapenv:Body>
</soapenv:Envelope>
```

Example response

```
<SOAP-ENV:Envelope SOAP-ENV:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:ns1="https://license.x-formation.com/soap/type/vendor/version/2"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/">
  <SOAP-ENV:Body>
    <ns1:ResetDeactivationCounterResponse>
      <return xsi:type="ns1:Soap_Response">
        <result_code xsi:type="xsd:int">0</result_code>
        <result_string xsi:nil="true"/>
      </return>
    </ns1:ResetDeactivationCounterResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```