

# LMX\_OPT\_AUTOMATIC\_HEARTBEAT\_ATTEMPTS

e O pti on	<p>LMX_OPT_AUTOMATIC_HEARTBEAT_ATTEMPTS</p> <p>This flag specifies whether automatic heartbeats are enabled and the maximum number of failed heartbeat attempts before LM-X shuts down the application.</p> <p>When this option is enabled and network licensing is used, a separate thread is started that performs automatic heartbeats once every 2 minutes. This interval can be changed using <a href="#">LMX_OPT_AUTOMATIC_HEARTBEAT_INTERVAL</a>.</p> <p>Setting the value to NULL will result in setting it to the default value.</p>
pS ett ing	<p>Possible values:</p> <p>An integer, as follows:</p> <p>-1 (Ignore failed heartbeat attempts. With this setting, your application will not shut down even if the license server goes down infinitely after a checkout. This setting is useful for a lenient license model. New instances of your application will not be able to start, but existing sessions will continue to run.)</p> <p>0 (Disabled. The client should perform manual heartbeats instead using <a href="#">LMX_Heartbeat()</a> to keep the license.</p> <p>&gt;0 (Shut down the application if no heartbeat response is received after the specified number of consecutive attempts. Once a valid heartbeat response is received, the internal counter will reset.)</p> <p>Default value:</p> <p>0 (disabled)</p>