

Performing a silent installation on Linux



This page refers to functionality that has been deprecated in License Statistics. See [Installing License Statistics on Linux](#).

You can run a silent (that is, unattended) installation of License Statistics at a command line using the following options.

Option	Description
-s	Start License Statistics after installation.
-t	Use trial license.
-p <i>port</i>	Web server port.
-n <i>service_name</i>	Service name (defaults to xflcstat).
-u <i>username</i>	Run as the specified user.
-k <i>activation_key</i>	An activation key.
-f <i>license_file_path</i>	License file path.
-r	Overwrite existing service.
-e accept reject	Accept or reject End User License Agreement.
-i <i>installation_directory</i>	Installation directory.
-h	Print this help message.

Example 1

The following example:

- Accepts the EULA
- Installs License Statistics to `${HOME}/licstat`
- Uses a trial license
- Configures the web server to listen on port 8080
- Installs the service under the name `licstat` and overwrites any existing service
- Starts License Statistics after installation

```
./license_statistics_v6.11.2_linux_x64.sh -- -e accept -i ${HOME}/licstat -t -p 8080 -n licstat -r -s
```

Example 2

The following example:

- Accepts the EULA
- Installs License Statistics to `/usr/licstat`
- Installs a service under the default name `xflcstat`
- Uses the license file `/tmp/license.lic`
- Configures the web server to listen on port 80

```
./license_statistics_v6.11.2_linux_x64.sh -- -e accept -i /usr/licstat -f /tmp/license.lic -p 80
```