

Logout

The Logout function is used to log a LAC administrator out of LAC using a token (created by the [Login](#) function).

Return values

On failure, the result string contains an error message. See [SOAP API return codes](#) for further information on error messages.

Example request

```
<soapenv:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:ns="https://license.x-formation.com/soap/type/vendor/version/1?wsdl">
    <soapenv:Header/>
    <soapenv:Body>
        <ns:Logout soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
            <token xsi:type="xsd:string">390bbf1a84283460a847b492843d96c57c5eff58</token>
        </ns:Logout>
    </soapenv:Body>
</soapenv:Envelope>
```

Example response

```
<SOAP-ENV:Envelope SOAP-ENV:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
<ns1:LogoutResponse>
    <return xsi:type="ns1:Soap_Response">
        <result_code xsi:type="xsd:int">0</result_code>
        <result_string xsi:nil="true"/>
    </return>
</ns1:LogoutResponse>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```