

DeactivateLicenseOrder

The DeactivateLicenseOrder function is used to deactivate a license.

This function requires an activation key, which can be obtained using the [GetLicenseOrderList](#) function, and a login token, which is obtained using the [Login](#) function.

Return values

On failure, the result string contains an error message. See [SOAP API return codes](#) for further information on error messages.

Example request

```
<soapenv:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:ns="https://license.x-formation.com/soap/type/vendor/version/1?wsdl">
  <soapenv:Header/>
  <soapenv:Body>
    <ns:DeactivateLicenseOrder soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
      <token xsi:type="xsd:string">e84b130bcd3fdf26644064098acdf9f3e5a3bfaa</token>
      <activationKey xsi:type="xsd:string">8YIVD-UGBMH-077N6-4TPD6</activationKey>
    </ns:DeactivateLicenseOrder>
  </soapenv:Body>
</soapenv:Envelope>
```

Example response

```
<SOAP-ENV:Envelope SOAP-ENV:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:ns1="https://license.x-formation.com/soap/type/vendor/version/1?wsdl"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/">
  <SOAP-ENV:Body>
    <ns1:DeactivateLicenseOrderResponse>
      <return xsi:type="ns1:Soap_Response">
        <result_code xsi:type="xsd:int">0</result_code>
        <result_string xsi:nil="true"/>
      </return>
    </ns1:DeactivateLicenseOrderResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```