

GetLicenseOrderLogList

The information on this page refers to SOAP version 4. This function did not exist in previous SOAP versions.

The GetLicenseOrderLogList function is used to get a license order log list.

This function uses an [offset](#) and requires a login token, which is obtained using the [Login](#) function.

Return values

The response is of the type [Soap_Response_List_LicenseOrderLog](#), with result_array of type [ArrayOfSoap_LicenseOrderLog](#).

Example request

```
<soapenv:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:ns="https://license.x-formation.com/soap/type/vendor/version/4">
  <soapenv:Header/>
  <soapenv:Body>
    <ns:GetLicenseOrderLogList soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
      <token xsi:type="xsd:string">ef817a73f8d19df33f6a84ae702c6da0d9edd309</token>
      <activationKey xsi:type="xsd:string">NZSQG-2067B-LTM9R-1784I</activationKey>
      <offset xsi:type="xsd:int">0</offset>
    </ns:GetLicenseOrderLogList>
  </soapenv:Body>
</soapenv:Envelope>
```

Example response

```
<SOAP-ENV:Envelope SOAP-ENV:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:ns1="https://license.x-formation.com/soap/type/vendor/version/4"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <SOAP-ENV:Body>
    <ns1:GetLicenseOrderLogListResponse>
      <return xsi:type="ns1:Soap_Response_List_LicenseOrderLog">
        <result_array SOAP-ENC:arrayType="ns1:Soap_LicenseOrderLog[2]"
          xsi:type="ns1:ArrayOfSoap_LicenseOrderLog">
          <item xsi:type="ns1:Soap_LicenseOrderLog">
            <time xsi:type="xsd:string">2019-02-12 09:19:53</time>
            <action xsi:type="xsd:string">Added</action>
            <user xsi:type="xsd:string">Demo Account</user>
            <hostname xsi:type="xsd:string">localhost</hostname>
            <ip_address xsi:type="xsd:string">127.0.0.1</ip_address>
            <hostids xsi:nil="true"/>
          </item>
          <item xsi:type="ns1:Soap_LicenseOrderLog">
            <time xsi:type="xsd:string">2019-02-13 08:32:47</time>
            <action xsi:type="xsd:string">Edited</action>
            <user xsi:type="xsd:string">Demo Account</user>
            <hostname xsi:type="xsd:string">localhost</hostname>
            <ip_address xsi:type="xsd:string">127.0.0.1</ip_address>
            <hostids xsi:nil="true"/>
          </item>
        </result_array>
        <result_code xsi:type="xsd:int">0</result_code>
        <result_string xsi:nil="true"/>
      </return>
    </ns1:GetLicenseOrderLogListResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```