

# GetProductTemplateById

The GetProductTemplateById function is used to get an existing product template using the product template ID.

This function also requires a login token, which is obtained using the [Login](#) function.

## Return values

The response is of the type [Soap\\_Response\\_ProductTemplate](#) with result\_object of type [Soap\\_ProductTemplate](#).

## Example request

```
<soapenv:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:ns="https://license.x-formation.com/soap/type/vendor/version/1?wsdl">
  <soapenv:Header/>
  <soapenv:Body>
    <ns:GetProductTemplateById soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
      <token xsi:type="xsd:string">24daaaaa6cad59284d831a9d7b36713c133d92d4</token>
      <id xsi:type="xsd:int">84</id>
    </ns:GetProductTemplateById>
  </soapenv:Body>
</soapenv:Envelope>
```

## Example response

```
<SOAP-ENV:Envelope SOAP-ENV:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:ns1="https://license.x-formation.com/soap/type/vendor/version/1?wsdl"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/">
  <SOAP-ENV:Body>
    <ns1:GetProductTemplateByIdResponse>
      <return xsi:type="ns1:Soap_Response_ProductTemplate">
        <result_object xsi:type="ns1:Soap_ProductTemplate">
          <id xsi:type="xsd:int">84</id>
          <name xsi:type="xsd:string">Test Template 1</name>
        </result_object>
        <result_code xsi:type="xsd:int">0</result_code>
        <result_string xsi:nil="true"/>
      </return>
    </ns1:GetProductTemplateByIdResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```